

Leuchtmittel SLS LED

Light Source SLS LED



Produkteigenschaften

- Abmessungen und Fassungen wie SLS T5
- Feldwinkel über **330°**
- Homogenes Leuchtbild, einzelne LED nicht sichtbar
- Verschiedene Farbtemperaturen
- Verschiedene Farbwiedergabeindizes (CRI)

Product Applications

- Dimensions and socket coincide with SLS T5 specifications
- Field angle > **330°** perfectly matches fluorescent versions
- Homogeneous, individual LED not visible
- Available in different colour temperatures
- Available in different CRI

Technische Daten Technical Data

Betriebsstrom Rated Current	195 mA
Temperaturbereich Temperature Range	ta = -20 °C ~ +40 °C
Lebensdauer Nominal Lifetime	50.000 h ta = +60°C L80B10
Abstrahlwinkel Beam Angle	260° FWHM
Sockel Socket	G5
Material Material	Glas Glass
Farbkonsistenz Colour Consistency	3 SDCM (3-step-McAdam)
Dimmbar Dimmable	Ja Yes
Energieeffizienzklasse Class of Energy Efficiency	E – G
Verpackungseinheit Packing Unit Quantities	10

Ausführung Model

⎓	■	CRI	l[m]	[V]	[W]	lm/W	📦	BestellNr.: Ordercode:
582 -2	3000	> 80	1500	54	10,5	143	80	6 O 169 00 0
582 -2	4000	> 80	1600	54	10,5	152	80	6 O 169 01 0
882 -2	3000	> 80	2245	83	16,0	144	120	6 O 258 10 0
882 -2	4000	> 80	2400	83	16,0	150	120	6 O 258 11 0
1182 -2	3000	> 80	3000	111	21,0	142	160	6 O 347 20 0
1182 -2	4000	> 80	3200	111	21,0	150	160	6 O 347 21 0
1402 -2	3000	> 80	3600	133	26,0	140	200	6 O 410 30 0
1402 -2	4000	> 80	3900	133	26,0	150	200	6 O 410 31 0
582 -2	2700	> 90	1190	55	10,7	111	80	6 O 155 02 1
582 -2	3000	> 90	1250	55	10,7	117	80	6 O 155 00 1
582 -2	4000	> 90	1370	55	10,7	128	80	6 O 155 01 1
582 -2	5000	> 90	1380	55	10,7	129	80	6 O 155 03 1
582 -2	6500	> 90	1380	55	10,7	129	80	6 O 155 04 1
882 -2	2700	> 90	1820	83	16,2	112	120	6 O 237 12 1
882 -2	3000	> 90	1910	83	16,2	118	120	6 O 237 10 1
882 -2	4000	> 90	2090	83	16,2	129	120	6 O 237 11 1
882 -2	5000	> 90	2110	83	16,2	130	120	6 O 237 13 1
882 -2	6500	> 90	2100	83	16,2	130	120	6 O 237 14 1
1182 -2	2700	> 90	2440	111	21,6	113	160	6 O 319 22 1
1182 -2	3000	> 90	2570	111	21,6	119	160	6 O 319 20 1
1182 -2	4000	> 90	2810	111	21,6	130	160	6 O 319 21 1
1182 -2	5000	> 90	2840	111	21,6	131	160	6 O 319 23 1
1182 -2	6500	> 90	2830	111	21,6	131	160	6 O 319 24 1
1402 -2	2700	> 90	2880	131	25,5	113	200	6 O 376 32 1
1402 -2	3000	> 90	3030	131	25,5	119	200	6 O 376 30 1
1402 -2	4000	> 90	3310	131	25,5	130	200	6 O 376 31 1
1402 -2	5000	> 90	3350	131	25,5	131	200	6 O 376 33 1
1402 -2	6500	> 90	3340	131	25,5	131	200	6 O 376 34 1

SLS LED	LED-Treiber LED driver			
	BestellNr.: Ordercode:			
	Non-dimmable: 3 C 180 08 0 018	DALI/ Touch Dim: 3 C 180 08 6 019	Non-dimmable: 3 C 130 01 0	DALI: 3 C 130 01 6
1 x 582			●	●
2 x 582	●	●	●	●
3 x 582	●	●		
4 x 582	●	●		
1 x 882	●	●	●	●
2 x 882	●	●		
3 x 882	●	●		
1 x 1182	●	●	●	●
2 x 1182	●	●		
1 x 1402	●	●	●	●
2 x 1402	●	●		

⎓ Länge in mm
Length in mm

■ Farbtemperatur in K
Colour temperature in K

📦 Gewicht in g
Weight in g

⎓ Leuchtmittel
Light Source

Datenblätter LED-Treiber ab Seite 12 und auf Anfrage
Data sheets LED driver from page 12 and on request