

Leuchtmittel T5 LED HE

Light Source T5 LED HE



Produkteigenschaften

- Ersatz für T5-Leuchtstofflampen HE (High Efficiency)
- Feldwinkel über **330°**
- Homogenes Leuchtbild, einzelne LED nicht sichtbar
- Verschiedene Farbtemperaturen
- Verschiedene Farbwiedergabeindizes (CRI)

Product Applications

- Replacement for T5 fluorescent lamps HE (High Efficiency)
- Field angle > **330°** perfectly matches fluorescent versions
- Homogeneous, individual LED not visible
- Available in different color temperatures
- Available in different CRI

Technische Daten Technical Data

Betriebsstrom Rated Current	195 mA
Temperaturbereich Temperature Range	ta = -20 °C ~ +60 °C
Lebensdauer Nominal Lifetime	50.000 h ta = +40°C L80B10
Abstrahlwinkel Beam Angle	260° FWHM
Sockel Socket	G5
Material Material	Glas Glass
Farbkonsistenz Colour Consistency	3 SDCM (3-step-McAdam)
Dimmbar Dimmable	Ja Yes
Energieeffizienzklasse Class of Energy Efficiency	E – G
Verpackungseinheit Packing Unit Quantities	25
Isolierung Insulation	330 V

T5 LED HE	LED-Treiber LED driver	
	Bestellnr.: Ordercode:	
	Non-dimmable: 3 C 180 08 0 018	DALI/ Touch Dim: 3 C 180 08 6 019
 2 x 549	●	●
3 x 549	●	●
4 x 549	●	●
1 x 849	●	●
2 x 849	●	●
3 x 849	●	●
1 x 1149	●	●
2 x 1149	●	●
1 x 1449	●	●
2 x 1449	●	●

Ausführung Model

		CRI	l[m]	[V]	[W]	lm/W		Bestellnr.: Ordercode:
549 -2	3000	> 80	1220	46	9,0	135	80	6 N 143 00 0
549 -2	4000	> 80	1310	46	9,0	145	80	6 N 143 01 0
849 -2	3000	> 80	1990	75	14,5	137	120	6 N 232 10 0
849 -2	4000	> 80	2120	75	14,5	146	120	6 N 232 11 0
1149 -2	3000	> 80	2750	103	20,0	137	160	6 N 321 20 0
1149 -2	4000	> 80	2940	103	20,0	147	160	6 N 321 21 0
1449 -2	3000	> 80	3520	131	25,5	138	200	6 N 410 30 0
1449 -2	4000	> 80	3750	131	25,5	147	200	6 N 410 31 0
549 -2	2700	> 90	1000	46	9,0	111	80	6 N 131 02 1
549 -2	3000	> 90	1050	46	9,0	116	80	6 N 131 00 1
549 -2	4000	> 90	1150	46	9,0	127	80	6 N 131 01 1
549 -2	5000	> 90	1160	46	9,0	128	80	6 N 131 03 1
549 -2	6500	> 90	1160	46	9,0	128	80	6 N 131 04 1
849 -2	2700	> 90	1630	75	14,5	112	120	6 N 213 12 1
849 -2	3000	> 90	1710	75	14,5	118	120	6 N 213 10 1
849 -2	4000	> 90	1870	75	14,5	129	120	6 N 213 11 1
849 -2	5000	> 90	1890	75	14,5	130	120	6 N 213 13 1
849 -2	6500	> 90	1890	75	14,5	130	120	6 N 213 14 1
1149 -2	2700	> 90	2260	103	20,0	113	160	6 N 294 22 1
1149 -2	3000	> 90	2370	103	20,0	118	160	6 N 294 20 1
1149 -2	4000	> 90	2590	103	20,0	129	160	6 N 294 21 1
1149 -2	5000	> 90	2620	103	20,0	131	160	6 N 294 23 1
1149 -2	6500	> 90	2610	103	20,0	130	160	6 N 294 24 1
1449 -2	2700	> 90	2880	131	25,5	113	200	6 N 376 32 1
1449 -2	3000	> 90	3030	131	25,5	119	200	6 N 376 30 1
1449 -2	4000	> 90	3310	131	25,5	130	200	6 N 376 31 1
1449 -2	5000	> 90	3350	131	25,5	131	200	6 N 376 33 1
1449 -2	6500	> 90	3340	131	25,5	131	200	6 N 376 34 1

 Länge in mm
Length in mm

 Farbtemperatur in K
Colour temperature in K

 Gewicht in g
Weight in g

 Leuchtmittel
Light Source

Datenblätter LED-Treiber ab Seite 12 und auf Anfrage
Data sheets LED driver from page 12 and on request