

Leuchtmittel T5 LED HO

Light Source T5 LED HO



Produkteigenschaften

- Ersatz für T5-Leuchtstofflampen HO (High Output)
- Feldwinkel über **330°**
- Homogenes Leuchtbild, einzelne LED nicht sichtbar
- Verschiedene Farbtemperaturen
- Verschiedene Farbwiedergabeindizes (CRI)

Product Applications

- Replacement for T5 fluorescent lamps HO (High Output)
- Field angle > **330°** perfectly matches fluorescent versions
- Homogeneous, individual LED not visible
- Available in different color temperatures
- Available in different CRI

Technische Daten Technical Data

Betriebsstrom Rated Current	250 mA
Temperaturbereich Temperature Range	ta = -20 °C ~ +60 °C
Lebensdauer Nominal Lifetime	50.000 h ta = +40°C L80B10
Abstrahlwinkel Beam Angle	260° FWHM
Sockel Socket	G5
Material Material	Glas Glass
Farbkonsistenz Colour Consistency	3 SDCM (3-step-McAdam)
Dimmbar Dimmable	Ja Yes
Energieeffizienzklasse Class of Energy Efficiency	E – G
Verpackungseinheit Packing Unit Quantities	25
Isolierung Insulation	330 V

Ausführung Model

⎓	■	CRI	l[m]	[V]	[W]	lm/W	📦	Bestellnr.: Ordercode:
549 -2	3000	> 80	1440	47	11,7	123	80	6 N 144 00 0
549 -2	4000	> 80	1680	47	11,7	144	80	6 N 168 01 0
849 -2	3000	> 80	2550	76	19,1	134	120	6 N 255 10 0
849 -2	4000	> 80	2720	76	19,1	143	120	6 N 272 11 0
1149 -2	3000	> 80	3530	105	26,2	135	160	6 N 353 20 0
1149 -2	4000	> 80	3770	105	26,2	144	160	6 N 377 21 0
1449 -2	3000	> 80	4510	133	33,3	135	200	6 N 451 30 0
1449 -2	4000	> 80	4810	133	33,3	144	200	6 N 481 31 0
549 -2	2700	> 90	1280	47	11,7	109	80	6 N 128 02 1
549 -2	3000	> 90	1350	47	11,7	115	80	6 N 135 00 1
549 -2	4000	> 90	1470	47	11,7	126	80	6 N 147 01 1
549 -2	5000	> 90	1490	47	11,7	127	80	6 N 149 03 1
549 -2	6500	> 90	1490	47	11,7	127	80	6 N 149 04 1
849 -2	2700	> 90	2090	76	19,1	110	120	6 N 209 12 1
849 -2	3000	> 90	2190	76	19,1	115	120	6 N 219 10 1
849 -2	4000	> 90	2400	76	19,1	126	120	6 N 240 11 1
849 -2	5000	> 90	2420	76	19,1	127	120	6 N 242 13 1
849 -2	6500	> 90	2420	76	19,1	127	120	6 N 242 14 1
1149 -2	2700	> 90	2900	105	26,2	111	160	6 N 290 22 1
1149 -2	3000	> 90	3040	105	26,2	116	160	6 N 304 20 1
1149 -2	4000	> 90	3320	105	26,2	127	160	6 N 332 21 1
1149 -2	5000	> 90	3360	105	26,2	128	160	6 N 336 23 1
1149 -2	6500	> 90	3350	105	26,2	128	160	6 N 335 24 1
1449 -2	2700	> 90	3690	133	33,3	111	200	6 N 369 32 1
1449 -2	3000	> 90	3880	133	33,3	116	200	6 N 388 30 1
1449 -2	4000	> 90	4240	133	33,3	127	200	6 N 424 31 1
1449 -2	5000	> 90	4290	133	33,3	129	200	6 N 429 33 1
1449 -2	6500	> 90	4280	133	33,3	128	200	6 N 428 34 1

T5 LED HO	LED-Treiber LED driver	
	Bestellnr.: Ordercode:	
⎓	Non-dimmable: 3 C 180 08 0 079	DALI/ Touch Dim: 3 C 180 08 6 065
2 x 549	●	●
3 x 549	●	●
4 x 549	●	●
1 x 849	●	●
2 x 849	●	●
3 x 849	●	●
1 x 1149	●	●
2 x 1149	●	●
1 x 1449	●	●
2 x 1449	●	●

⎓ Länge in mm
Length in mm

■ Farbtemperatur in K
Colour temperature in K

📦 Gewicht in g
Weight in g

⎓ Leuchtmittel
Light Source

Datenblätter LED-Treiber ab Seite 12 und auf Anfrage
Data sheets LED driver from page 12 and on request