

# Leuchtmittel SLS LED

## Light Source SLS LED



### Produkteigenschaften

- Abmessungen und Fassungen wie SLS T5
- Abstrahlwinkel über **330°**
- Homogenes Leuchtbild
- Lichtausbeute ca. **160 lm/W**
- Verschiedene Lichtfarben

### Product Applications


- Dimensions and socket coincide with SLS T5 specifications
- Beam Angle > **330°** perfectly matches fluorescent versions
- Homogenous, LED not visible
- Efficacy about **160 lm/W**
- Available in different light temperatures and colours.



### Technische Daten

#### Technical Data

Lampe Lamp	SLS LED
Betriebsstrom Rated current	194 mA
Temperaturbereich Temperature Range	ta = -20 °C – +40 °C
Lebensdauer Nominal Lifetime	50.000 h @ ta max. L80B10
Lichtausbeute Efficacy	~160 lm/W *
Halbwertswinkel Rated beam angle (half peak value)	260°
Sockel Socket	G5
Material Material	Glas Glass
Farbkonsistenz Colour consistency	3 SDCM (3-step-McAdam)
Dimmbar Dimmable	Ja Yes
Energieeffizienzklasse Class of Energy Efficiency	A++
Verpackungseinheit Packing Unit Quantities	10
Maß D [mm ±1 mm] Size D [mm±1 mm]	36,00
Maß F [mm ±1 mm] Size F [mm±1 mm]	50,00
Maß G [mm ±1 mm] Size G [mm±1 mm]	8,00
Maß E [mm max.] Size E [mm max.]	16,20

\* Wert kann je nach Leuchtmittel variieren \* Values can vary depending upon lamp



—	A mm min.	l[m]	[V]	[W]	lm/W	CRI			Bestellnr.: Ordercode:
582 -2	481	1500	54	10,5	143	> 80	3000	85 g	6 O 169 00 0
582 -2	481	1600	54	10,5	152	> 80	4000	85 g	6 O 169 01 0
882 -2	781	2245	83	16,0	144	> 80	3000	130 g	6 O 258 10 0
882 -2	781	2400	83	16,0	150	> 80	4000	130 g	6 O 258 11 0
1182 -2	1081	3000	111	21,0	142	> 80	3000	175 g	6 O 347 20 0
1182 -2	1081	3200	111	21,0	150	> 80	4000	175 g	6 O 347 21 0
1402 -2	1301	3600	133	26,0	140	> 80	3000	200 g	6 O 410 30 0
1402 -2	1301	3900	133	26,0	150	> 80	4000	200 g	6 O 410 31 0
<hr/>									
582 -2	481	1190	55	10,7	111	> 90	2700	85 g	6 O 155 02 1
582 -2	481	1250	55	10,7	117	> 90	3000	85 g	6 O 155 00 1
582 -2	481	1370	55	10,7	128	> 90	4000	85 g	6 O 155 01 1
582 -2	481	1380	55	10,7	129	> 90	5000	85 g	6 O 155 03 1
582 -2	481	1380	55	10,7	129	> 90	6500	85 g	6 O 155 04 1
882 -2	781	1820	83	16,2	112	> 90	2700	130 g	6 O 237 12 1
882 -2	781	1910	83	16,2	118	> 90	3000	130 g	6 O 237 10 1
882 -2	781	2090	83	16,2	129	> 90	4000	130 g	6 O 237 11 1
882 -2	781	2110	83	16,2	130	> 90	5000	130 g	6 O 237 13 1
882 -2	781	2100	83	16,2	130	> 90	6500	130 g	6 O 237 14 1
1182 -2	1081	2440	111	21,6	113	> 90	2700	175 g	6 O 319 22 1
1182 -2	1081	2570	111	21,6	119	> 90	3000	175 g	6 O 319 20 1
1182 -2	1081	2810	111	21,6	130	> 90	4000	175 g	6 O 319 21 1
1182 -2	1081	2840	111	21,6	131	> 90	5000	175 g	6 O 319 23 1
1182 -2	1081	2830	111	21,6	131	> 90	6500	175 g	6 O 319 24 1
1402 -2	1301	2880	131	25,5	113	> 90	2700	200 g	6 O 376 32 1
1402 -2	1301	3030	131	25,5	119	> 90	3000	200 g	6 O 376 30 1
1402 -2	1301	3310	131	25,5	130	> 90	4000	200 g	6 O 376 31 1
1402 -2	1301	3350	131	25,5	131	> 90	5000	200 g	6 O 376 33 1
1402 -2	1301	3340	131	25,5	131	> 90	6500	200 g	6 O 376 34 1

— Länge in mm  
Length in mm

Typische Farbtemperatur in Kelvin  
Typical colour temperature in Kelvin

Gewicht  
Weight